

ORANGE COUNTY'S FLORIDAN AQUIFER DRAINAGE WELLS

Recent Experience & Proactive Rehabilitation Program



Water Resources
Technical Group
Luncheon



When: Thursday, February 18th

Where: Marriott Downtown,
400 West Livingston Ave

Presented by:

- Devo Seereeram, Ph.D., P.E.
Principal Engineer
Devo Engineering
- Maricela Torres
Chief Engineer
Orange County Public Works Dept.
(Roads & Drainage Division)
- Dave Kincaid, P.G.
Hydrogeology Manager
Devo Engineering
- Duane Watroba
Permitting Compliance and
Enforcement
FDEP (Central District), UIC Program

Outline of Presentation:

This presentation focuses on the critical subject of drainage well replacement and rehabilitation in Orange County and includes the perspectives of the Owner (Orange County), the regulatory agency (FDEP), and the consultant.

Orange County

Short and long range plans/approach for well inspection, maintenance, and replacement; Design philosophy for well replacement projects with some examples and budgeting the replacements well projects.

FDEP


State and Federal regulations which apply to these well replacement projects; typical research and design phases in the justification process to gain approval, including post-construction certification.

Devo Engineering (Consultant)

History of drainwells in Central Florida; Design and permitting consideration; discuss special problems encountered during well construction, how to handle emergency projects; Importance of wells on lake hydrology, flood control, & aquifer recharge, and present some significant success stories in Orange County.

Introductory Remarks:

- Nationwide: there are about 71,000 documented stormwater drainage wells, with an estimated total of about 248,000 wells when the undocumented wells are counted. 81% of the documented wells are in 7 western states (Washington, Arizona, Idaho, Oregon, Montana, California, and Utah, with the first mentioned having the most).
- Florida: 2,153 documented wells, with about 200 to 250 of these being lake level control wells.
- Floridan Aquifer wells in state of Florida: 607 records are available; note: these do not include Biscayne aquifer wells located in Broward and Dade County.
- Distribution of Floridan aquifer drainage wells within the state:
 1. Orlando area = 392 wells (highest density of drainage wells within the state)
 2. Live Oak area = 46 wells
 3. Ocala area = 35 wells
- Well diameters range from 6" to 24" are they are in the Upper Floridan aquifer; street wells are usually 12" in diameter or less




General Distribution of Drainage Wells and Interaquifer Connector Wells

- EXPLANATION**
- 12-F Number of Floridan Aquifer Drainage Wells in County
 - 2000 -B Number of Biscayne Aquifer Drainage Wells in County
 - 101- IC Number of Interconnector Drainage Wells in County


Adapted from: Kimrey & Fayard, 1984

Floridan Aquifer Drainage Wells in Orlando Area




Adapted from: Kimrey & Fayard, 1984

Generalized Hydrogeologic Section in the Orlando Area




Public water supply withdrawals in Orange County/Orlando near drainage wells are completed into the Lower Floridan Aquifer - Adapted from: Bradner 1991

Injection Well Classes



Underground Source of Drinking Water (USDW)
An aquifer or its portion which:
1. Supplies drinking water for human consumption; or
2. Contains water with a total dissolved solids (TDS) concentration of less than 10,000 mg/l; and
3. Is not an exempted aquifer.

FDEP website Graphic, 62-528




Typical Municipal Injection Well Construction

Casing	Outside Diameter	Wall Thickness	Typical Length	Material
Surface	52"	3/8"	100-250'	Steel
Shallow Intermediate	42"	3/8"	900-1000'	Steel
Deep Intermediate*	34"	3/8"	1500-2100'	Steel
Injection	24"	1/2"	2400-3000'	Seamless Steel

* The deep intermediate casing is set below the base of the lowermost underground source of drinking water.

Casing depths apply only to Southeast Florida.

FDEP website Graphic, 62-528



FDEP 02/2001

Typical Municipal Class I Injection Well, ASR Well and Water Well in Southeast Florida


FDEP website Graphic, 62-528

Types of Floridan Aquifer Drainage Wells in Central Florida:

- Direct street runoff drainage wells
- Lake level control wells
- Pond level control wells
- Canal level control wells
- Local area drainage wells

Typical Lake Level Control Well


Weir Inlet Structure - Typically



For "Old" Wells,
A small concrete box
w/ rebar grating

For "New" Wells,
A corrugated steel beehive
w/ Angle-Iron grating

Removable board to
adjust lake level



Manhole: Frequently
is buried, inaccessible
or unlocateable

Lake


Land

Weir Inlet Structure

Well

Adapted from: McBee, 1985

Typical Direct street runoff drainage wells



Adapted from: McBee, 1985

Drainage Well Chronology for Central Florida (1 of 4):

1904 - The first drainage well in Orange County was drilled. In April of that year, a sinkhole (probably Lake Greenwood) became clogged and a considerable area in southeastern Orlando was flooded by heavy rains. After several unsuccessful attempts to reopen the sink (including blasting), a drainage well was drilled as an experiment. In August, a two-inch test well was drilled, and it proved successful enough to warrant the construction of larger wells. The next year two more wells, one 8-inch and one 12-inch, were completed and these drained a large part of the flooded area. These wells, however, were not sufficient to drain the area completely, so in the winter of 1906 two more 12-inch wells were constructed, and by February 1907, a fourth 12-inch well had been completed. By the end of March 1907, the water was almost back to its normal level.

1906 - 6 wells documented

Following success of Lake Greenwood drainage, these wells became the commonly accepted solution to drainage problems in the Orlando area.

1910 - Lake Fairview well started geysering on Sep 26 of that year (3 years after it was constructed) and became a local attraction in 1912. it was subsequently plugged.



Photographer H. A. Abercromby recorded this flooded section of Orlando sometime in the **1880's** and **1890's**, according to Florida State Archives records. During heavy rains, the area near Greenwood Cemetery and the black community of Jonestown, east of downtown Orlando, was especially prone to flooding.

Drainage Well Chronology for Central Florida (2 of 4):

1926, 1928 - A large number of drainage wells were installed to deal with the excessively heavy rains in these years.

1936 - 120 wells documented (90 owned by the city and 30 owned by the county)

1939 - Permits became required to dig drainage wells

1943 - 200 wells documented (used their water elevations to construct a detailed pot surface map of the Orlando area and showed that the aquifer level rises very quickly due to drainage well recharge, 6 ft rise in 30 hr)

1948, 1954, 1959 - Drainage-well construction was accelerated again during these wetter-than-average years

1960 (Hurricane Donna) - Highest rate ever of drainage-well construction (35 wells during 1960)

Flooded Hiawassee Road from heavy rainfall and ineffectiveness of drainage well 1930



This photo was taken before Hiawassee Rd was realigned


Lake Davis in southwest section of Orlando seen flooded after heavy rain 1930



Rig in photograph was used to drill deeper drainage well



Orlando's "spouting well" on Lake Fairview, seen in **1934**, first became a local attraction about 1912. The geyser, which shot water 75 to 100 feet in the air, was on the Davis-McNeill farm on the lake's south side and was the result of a well drilling that unintentionally hit the great underground Floridan aquifer. Farm manager R.D. Eunice asked a small admission fee for the curious, and folks who didn't want to pay just parked their cars across the lake and waited out the interval between spouts. The well has been capped for many years.



Methane gas burning from newly drilled drainage well

Height of flame is between 80 and 100 ft. at 9:00 a.m., Friday, , March 12, **1948**. Gas flowed at a land surface depth of 100 ft.

Located on 31st and S. Westmoreland.



Water shoots about 40 feet high toward the tall pine trees on March 12, **1948**, at South Westmoreland Drive and 31st Street in Orlando in an image from the Florida Geological Survey Collection. The temporary spout occurred during the drilling of a drainage well.

Drainage Well Chronology for Central Florida (3 of 4):

1964 - An excessively wet year and the available records indicate that drainage-well construction was intensified as a result.

1965 - The Florida State Board of Health stopped granting permits for construction of new drainage wells. However, replacement of existing wells was still allowed.

1970's - The state stopped granting permits for the construction of any drainage wells including replacement wells.


1977 - 412 wells documented

1981 - 392 wells documented

1985 - 413 wells documented on USGS listing


1987, 1988 - USGS performs study of groundwater chemistry in vicinity of selected drainage wells in Orlando and compares to background groundwater quality.

10-day Antecedent Rainfall (ORLANDO)




Orlando Rainfall Peaks Coincide with Active Drainage well Construction – 10 Day Peaks

31 Day Antecedent Rainfall (ORLANDO)



Orlando Rainfall Peaks Coincide with Active Drainage well Construction – Monthly Peaks



Orlando Rainfall Peaks Coincide with Active Drainage well Construction – Annual Peaks

Drainage Well Chronology for Central Florida (4 of 4):

1997 - Under Chapter 403.088 Florida Statutes, FDEP started reviewing and approving drainage well replacement projects which would improve water quality. Lake Tennessee drainage well replaced by City of Orlando. Lake's water quality (TSI) seems to have improved since well replacement due to flush rate.


1998 (El Nino rains) - Orange County replaced the Lake Azalea drainwells in early part of 1998, then Lake Lilly drainwell right after, and Banana Bay and Daniels Road (SR 535) drainage wells in 1999. Numerous other wells have been replaced by the county since Lake Azalea. Orlando has replaced 9 wells.

2003 - Updated well inventory performed by SFWMD contractor (Hartman); 494 well records available with 475 of these 494 wells within Orange County. 411 wells are maintained by government agencies.

City of Orlando is responsible for 261 wells while Orange County is responsible for 71 wells.

2006 - Central Florida Aquifer Recharge Enhancement Program, Artificial Recharge Well Demonstration Project by CH2M Hill. Drainage wells: Sherwood, Orienta, Festival Park. oxygen-laden recharge water or change in carbonate balance mobilizing arsenic from dissolution of pyrite. Arsenic standard changed in Jan 2005 from 50 ppb to 10 ppb and all samples were lower than 20 ppb. No synthetic organics and coliform reduction of 2 to 6 orders. Coliform bacteria appears to have acclimatized in Floridan aquifer. Lake Sherwood not sampled since the well rarely flows.

Lake Tennessee TSI



Summary of Status of Drainage Wells of Four Municipal Owners, Central Florida:

Owner	Number of Wells				
	Street or Urban Drainage	Lake-Level Control	Inactive (Plugged or Capped)	Status Unknown or Unlocated	Total
City of Orlando	80	52	37*	60*	229
Orange County	24	51	2	0	77
City of Ocoee	0	5	0	2	7
City of Altamonte Springs	0	2	0	0	2
Total	104	110	39	62	315

Adapted from: McBee, 1985

Distribution of Diameter of Drainage Wells:

Well Diameter (Inches)	Lake1	Storm2	Alone3	Size Total
6"	2	6	3	11
8"	7	8	3	18
10"	4	12	3	19
12"	35	57	5	97
14"	3	1	1	5
16"	1	1	0	2
18"	10	8	1	19
20"	19	13	0	32
24"	0	1	0	1
Not Given	3	1	0	4
Totals	84	108	16	200

Depths of Drainage Wells and Public-Supply Wells, Central Florida:

Well Type	Number of Wells	Range of Depth (feet)	Percent of wells in which indicated depth is exceeded				
			90	75	50	25	10
Drainage	314	120-1,049	196	334	424	484	600
Public Supply	186*	94-1,500	200	324	420	558	1,300

Adapted from: McBee, 1985

View of Morning Glory Spillway



Values of Theoretical Acceptance Rates for Drainage Wells (Morning Glory Hydraulics):

Well Diameter in Inches	0.05'	0.10'	0.18'	0.25'	0.50'	1.00'
6	31.5	82.5	159	194	274	776
8	42.7	113.3	245	326	487	1024
10	54.3	148.0	335	489	775	1303
12	66.2	178.4	404	626	1097	1551
14	76.8	212.1	475	757	1446	2126
16	88.7	245.0	554	886	1843	2606
18	99.3	274.2	646	1013	2318	3490
20	109.9	303.5	733	1127	2731	4330
24	132.4	365.7	883	1393	3540	6205

Adapted from: McBee, 1985

Theoretical Acceptance Rates for Drainage Wells (Based on Aquifer Transmissivity)

A. $T = 500,000 \text{ gpd/ft} = 0.5 \text{ MGD/ft}$

Adapted from: McBee, 1985

Diameter (Inches)	Full Penetration ($p=1.0$)		60% Penetration ($p=0.60$)		6% Penetration ($p=0.06$)	
	(GPM)	(MGD)	(GPM)	(MGD)	(GPM)	(MGD)
6	545	0.79	327	0.47	32.7	0.05
8	727	1.05	436	0.63	43.6	0.06
10	909	1.31	545	0.79	54.5	0.08
12	1,091	1.57	654	0.94	65.4	0.09
14	1,273	1.83	764	1.10	76.4	0.11
16	1,454	2.09	873	1.26	87.3	0.13
18	1,636	2.36	982	1.41	98.2	0.14
20	1,818	2.62	1,091	1.57	109	0.16
24	2,182	3.14	1,309	1.88	131	0.19

Theoretical Acceptance Rates for Drainage Wells (Based on Aquifer Transmissivity)

B. $T = 750,000 \text{ gpd/ft} = 0.75 \text{ MGD/ft}$

Adapted from: McBee, 1985

Diameter (Inches)	Full Penetration ($p=1.0$)		60% Penetration ($p=0.60$)		6% Penetration ($p=0.06$)	
	(GPM)	(MGD)	(GPM)	(MGD)	(GPM)	(MGD)
6	818	1.18	491	0.71	49.1	0.07
8	1,091	1.57	654	0.94	65.4	0.09
10	1,364	1.96	818	1.18	81.8	0.12
12	1,636	2.36	982	1.41	98.2	0.14
14	1,909	2.75	1,145	1.65	115	0.16
16	2,182	3.14	1,309	1.88	131	0.19
18	2,454	3.53	1,473	2.12	147	0.21
20	2,727	3.93	1,636	2.36	164	0.24
24	3,272	4.71	1,963	2.83	196	0.28

Recharge Contribution of Drainage Wells to Upper Floridan Aquifer, Central Florida:

- Estimated recharge contribution of drainage wells: 40 to 50 mgd in Orlando area.
- If all wells are plugged, the potentiometric surface of the Upper Floridan aquifer is predicted to decline by 4 ft.
- This recharge water (from lake level control wells) should be considered a viable Alternative Water Supply.

Parameters which typically exceed Primary and Secondary Drinking Water Standards in Lake Water:


- Total Coliform (always exceeded) but there is no evidence of contamination although it has been exceeded for over 100 years (since 1906). Our experience indicates that these 2 parameters are exceeded:
 - Color
 - Total Coliform.

- Lead and Cadmium for some street wells; lead decreasing due to use of unleaded gasoline.

Known Contamination Events tied to Floridan aquifer drainage wells in Central Florida:

There is no documented evidence of significant aquifer contamination caused by recent drainage well operations in Orange or Seminole counties.

- **1961:** Lake Pleasant (near Apopka) - during high water of 1961, muddy water showed up in the nearby Northcrest public water supply well located about 1000 ft from the drainage well. delay time was hours. Muddy conditions, high in bacteria, and unpleasant taste and odor.
- **1993:** Lake Orienta (Altamonte Springs) - 1993 drinking water wells around the lake were reportedly contaminated. City abandoned 2 Upper Floridan potable wells at WTP 2 in 1995 due to high bacteria and replaced with Lower Floridan wells.
- **1998:** Lake Johio (Ocoee) - during high flow following El Nino storms in 1998, there was lake debris entering the well and impacting nearby residential wells. The subject drainwell was apparently blocked by Orange County sometime in the past (prior to 1980) due to complaints of "muddy water" from the nearby residents. The fitting that was used to block the flow into the drainwell apparently deteriorated and the well started flowing when the El-Nino rains hit early in 1998. complaints of air, lake vegetation debris, etc. the problem did not occur during low flow conditions or when a bleed-down was installed.



Lake Orienta
Drainage Wells &
Adjacent Public
Supply Wells

Public Supply Wells and Private Supply Wells
Within 1 Mile of Recharge Wells

Source: SJRWMD SP SJ2007-SP11

Lake Johio (lake contamination)



Pump House on Barnett Property During High Water Stage A Few Days Before Hurricane Donna in 1960 - Source: Ms. Pat Barnett

Lake Johio (lake contamination)



Pump House on Barnett Property During High Water Stage (Not Peak) A Few Days Before Hurricane Donna in 1960 - Source: Ms. Pat Barnett


Case Study # 1

Lake Sherwood

(Effective Lake Level Control)



Lake Sherwood's Watershed Limits



Lake Sherwood's Drainage Well Replacement Project – A Quiet Success Story (1 of 2):

Lake Sherwood is a land-locked lake in western Orange County (FL).

It is the terminal point of a chain of interconnected lakes which include Lake Lotta, Lake Rose, and Steer Lake, with a combined watershed area of over 4,500 acres.

Development is progressing rapidly within the 4,500+ acre watershed and citrus groves are being transformed into residential and commercial land uses (i.e., additional impervious area).

Given the sheer size of this watershed (>4,500 acres) and its urban land cover, Lake Sherwood's drainage well is perhaps the most critical drainage well in Orange County.

The maximum recorded lake stage was approximately +88 ft NGVD in October 1960 following Hurricane Donna; the minimum was approximately +55 ft NGVD in December 1981 following a period of record drought. A recorded fluctuation range of over 33 ft.

Lake Sherwood's Drainage Well Replacement Project – A Quiet Success Story (2 of 2):

During the high water period of 1960, numerous homes on the north side of the lake were flooded for almost a year. As a result of the 1960 flooding, a 24-inch diameter drainage well was installed to discharge water from Lake Sherwood to the underlying Floridan aquifer. Water flows from the lake into the drainwell when the lake stage exceeds +76.9 ft NGVD. At the present time, there are no other outfalls from this "closed" lake other than the drainwell.

Following the 2004 Hurricanes, the lake level rose again and an emergency permit from the FDEP was sought and approved to replace this well since it was in a difficult location to maintain and there was evidence of holes in the well casing. The 24-inch diameter well was replaced with four (4) 12-inch diameter wells at a location approximately 2,500 feet southeast of the existing well.

These replacement wells came online in July 2005.


The replacement wells were tested during the storm of May 2009 (i.e., Gulf Gale).

Rainfall Data Representative of Lake Sherwood's Watershed for May 2009 storm		
Date	Ocoee (inch)	Windermere (inch)
Wednesday, May 13, 2009	1.83	0.29
Thursday, May 14, 2009	0.00	0.00
Friday, May 15, 2009	0.15	0.21
Saturday, May 16, 2009	0.00	0.00
Sunday, May 17, 2009	0.00	0.00
Monday, May 18, 2009	0.40	0.71
Tuesday, May 19, 2009	4.91	3.60
Wednesday, May 20, 2009	3.52	4.93
Thursday, May 21, 2009	2.61	2.50
Friday, May 22, 2009	0.11	0.18
Saturday, May 23, 2009	0.72	0.77
Sunday, May 24, 2009	0.68	0.55
Monday, May 25, 2009	2.52	1.55
Tuesday, May 26, 2009	0.01	0.28
Wednesday, May 27, 2009	0.76	1.22
Thursday, May 28, 2009	1.17	0.00
Friday, May 29, 2009	0.47	0.95
Saturday, May 30, 2009	0.06	0.00
Totals.	19.92	17.74


Rainfall Data Representative of Lake Sherwood's Watershed for May 2009 Storm

The lake level rose 6 ft over the 3 days May 19 to May 21 and caused a cofferdam failure which led to the shut down of a lane on State Road 50 due to undermining.

The wells kicked in and performed a remarkable job of controlling the lake level. see video and chart.



Lake Sherwood - Lake Level Plot (1960 to Sept 2009)





Video captured 07-13-09

Lake Sherwood Video of Wells for July 2009


Case Study # 2

Lake Holden

(Geysering)



Lake Holden
Drainage Well
Replacement Plan



Lake Holden (geysering)



Video captured 12-15-09

Lake Holden
(geysering)



Video captured 12-21-09

Lake Holden
(geysering)

Case Study # 3

Goddard Ave

(Deep Muck)



1-View of 2,000 pound pneumatic hammer used to drive 16-inch dia. surface casing



2-View of 16-inch dia. surface casing installation



3-View of 16-inch diameter drill bit used to drill borehole below surface casing in order to set 10-inch well casing



4-View of 10-inch dia. well casing being placed through annulus of surface casing to a depth of 150 ft



5-View of packer and grout pipe being set to through well casing for pressure grouting annulus




Illustration of Hydrogeologic Anomalies Encountered With Installation of Goodard Ave Drainage Well and Proposed Solution



6-View of setting grout pipe at bottom of casing and sealing wellhead for pressure grouting



7-View of cement pump during grout injection



8-View of 99-inch dia. drill bit used to drill open borehole opening

DEVO Engineering
 Illustration of Hydrogeologic Anomalies Encountered With Installation of Goodard Ave Drainage Well and Proposed Solution
 GODDARD AVENUE
 508 462 6622 65-66-67 68-69-70 71-72-73 74-75-76 77-78-79 80-81-82 83-84-85-86 87-88-89 90-91-92 93-94-95 96-97-98 99-100-101 102-103-104 105-106-107 108-109-110 111-112-113 114-115-116 117-118-119 120-121-122 123-124-125 126-127-128 129-130-131 132-133-134 135-136-137 138-139-140 141-142-143 144-145-146 147-148-149 150-151-152 153-154-155 156-157-158 159-160-161 162-163-164 165-166-167 168-169-170 171-172-173 174-175-176 177-178-179 180-181-182 183-184-185 186-187-188 189-190-191 192-193-194 195-196-197 198-199-200 201-202-203 204-205-206 207-208-209 210-211-212 213-214-215 216-217-218 219-220-221 222-223-224 225-226-227 228-229-230 231-232-233 234-235-236 237-238-239 240-241-242 243-244-245 246-247-248 249-250-251 252-253-254 255-256-257 258-259-260 261-262-263 264-265-266 267-268-269 270-271-272 273-274-275 276-277-278 279-280-281 282-283-284 285-286-287 288-289-290 291-292-293 294-295-296 297-298-299 300-301-302 303-304-305 306-307-308 309-310-311 312-313-314 315-316-317 318-319-320 321-322-323 324-325-326 327-328-329 330-331-332 333-334-335 336-337-338 339-340-341 342-343-344 345-346-347 348-349-350 351-352-353 354-355-356 357-358-359 360-361-362 363-364-365 366-367-368 369-370-371 372-373-374 375-376-377 378-379-380 381-382-383 384-385-386 387-388-389 390-391-392 393-394-395 396-397-398 399-400-401 402-403-404 405-406-407 408-409-410 411-412-413 414-415-416 417-418-419 420-421-422 423-424-425 426-427-428 429-430-431 432-433-434 435-436-437 438-439-440 441-442-443 444-445-446 447-448-449 450-451-452 453-454-455 456-457-458 459-460-461 462-463-464 465-466-467 468-469-470 471-472-473 474-475-476 477-478-479 480-481-482 483-484-485 486-487-488 489-490-491 492-493-494 495-496-497 498-499-500 501-502-503 504-505-506 507-508-509 510-511-512 513-514-515 516-517-518 519-520-521 522-523-524 525-526-527 528-529-530 531-532-533 534-535-536 537-538-539 540-541-542 543-544-545 546-547-548 549-550-551 552-553-554 555-556-557 558-559-560 561-562-563 564-565-566 567-568-569 570-571-572 573-574-575 576-577-578 579-580-581 582-583-584 585-586-587 588-589-590 591-592-593 594-595-596 597-598-599 600-601-602 603-604-605 606-607-608 609-610-611 612-613-614 615-616-617 618-619-620 621-622-623 624-625-626 627-628-629 630-631-632 633-634-635 636-637-638 639-640-641 642-643-644 645-646-647 648-649-650 651-652-653 654-655-656 657-658-659 660-661-662 663-664-665 666-667-668 669-670-671 672-673-674 675-676-677 678-679-680 681-682-683 684-685-686 687-688-689 690-691-692 693-694-695 696-697-698 699-700-701 702-703-704 705-706-707 708-709-710 711-712-713 714-715-716 717-718-719 720-721-722 723-724-725 726-727-728 729-730-731 732-733-734 735-736-737 738-739-740 741-742-743 744-745-746 747-748-749 750-751-752 753-754-755 756-757-758 759-760-761 762-763-764 765-766-767 768-769-770 771-772-773 774-775-776 777-778-779 780-781-782 783-784-785 786-787-788 789-790-791 792-793-794 795-796-797 798-799-800 801-802-803 804-805-806 807-808-809 810-811-812 813-814-815 816-817-818 819-820-821 822-823-824 825-826-827 828-829-830 831-832-833 834-835-836 837-838-839 840-841-842 843-844-845 846-847-848 849-850-851 852-853-854 855-856-857 858-859-860 861-862-863 864-865-866 867-868-869 870-871-872 873-874-875 876-877-878 879-880-881 882-883-884 885-886-887 888-889-890 891-892-893 894-895-896 897-898-899 900-901-902 903-904-905 906-907-908 909-910-911 912-913-914 915-916-917 918-919-920 921-922-923 924-925-926 927-928-929 930-931-932 933-934-935 936-937-938 939-940-941 942-943-944 945-946-947 948-949-950 951-952-953 954-955-956 957-958-959 960-961-962 963-964-965 966-967-968 969-970-971 972-973-974 975-976-977 978-979-980 981-982-983 984-985-986 987-988-989 990-991-992 993-994-995 996-997-998 999-1000-1001 1002-1003-1004 1005-1006-1007 1008-1009-1010 1011-1012-1013 1014-1015-1016 1017-1018-1019 1020-1021-1022 1023-1024-1025 1026-1027-1028 1029-1030-1031 1032-1033-1034 1035-1036-1037 1038-1039-1040 1041-1042-1043 1044-1045-1046 1047-1048-1049 1050-1051-1052 1053-1054-1055 1056-1057-1058 1059-1060-1061 1062-1063-1064 1065-1066-1067 1068-1069-1070 1071-1072-1073 1074-1075-1076 1077-1078-1079 1080-1081-1082 1083-1084-1085 1086-1087-1088 1089-1090-1091 1092-1093-1094 1095-1096-1097 1098-1099-1100 1101-1102-1103 1104-1105-1106 1107-1108-1109 1110-1111-1112 1113-1114-1115 1116-1117-1118 1119-1120-1121 1122-1123-1124 1125-1126-1127 1128-1129-1130 1131-1132-1133 1134-1135-1136 1137-1138-1139 1140-1141-1142 1143-1144-1145 1146-1147-1148 1149-1150-1151 1152-1153-1154 1155-1156-1157 1158-1159-1160 1161-1162-1163 1164-1165-1166 1167-1168-1169 1170-1171-1172 1173-1174-1175 1176-1177-1178 1179-1180-1181 1182-1183-1184 1185-1186-1187 1188-1189-1190 1191-1192-1193 1194-1195-1196 1197-1198-1199 1200-1201-1202 1203-1204-1205 1206-1207-1208 1209-1210-1211 1212-1213-1214 1215-1216-1217 1218-1219-1220 1221-1222-1223 1224-1225-1226 1227-1228-1229 1230-1231-1232 1233-1234-1235 1236-1237-1238 1239-1240-1241 1242-1243-1244 1245-1246-1247 1248-1249-1250 1251-1252-1253 1254-1255-1256 1257-1258-1259 1260-1261-1262 1263-1264-1265 1266-1267-1268 1269-1270-1271 1272-1273-1274 1275-1276-1277 1278-1279-1280 1281-1282-1283 1284-1285-1286 1287-1288-1289 1290-1291-1292 1293-1294-1295 1296-1297-1298 1299-1300-1301 1302-1303-1304 1305-1306-1307 1308-1309-1310 1311-1312-1313 1314-1315-1316 1317-1318-1319 1320-1321-1322 1323-1324-1325 1326-1327-1328 1329-1330-1331 1332-1333-1334 1335-1336-1337 1338-1339-1340 1341-1342-1343 1344-1345-1346 1347-1348-1349 1350-1351-1352 1353-1354-1355 1356-1357-1358 1359-1360-1361 1362-1363-1364 1365-1366-1367 1368-1369-1370 1371-1372-1373 1374-1375-1376 1377-1378-1379 1380-1381-1382 1383-1384-1385 1386-1387-1388 1389-1390-1391 1392-1393-1394 1395-1396-1397 1398-1399-1400 1401-1402-1403 1404-1405-1406 1407-1408-1409 1410-1411-1412 1413-1414-1415 1416-1417-1418 1419-1420-1421 1422-1423-1424 1425-1426-1427 1428-1429-1430 1431-1432-1433 1434-1435-1436 1437-1438-1439 1440-1441-1442 1443-1444-1445 1446-1447-1448 1449-1450-1451 1452-1453-1454 1455-1456-1457 1458-1459-1460 1461-1462-1463 1464-1465-1466 1467-1468-1469 1470-1471-1472 1473-1474-1475 1476-1477-1478 1479-1480-1481 1482-1483-1484 1485-1486-1487 1488-1489-1490 1491-1492-1493 1494-1495-1496 1497-1498-1499 1500-1501-1502 1503-1504-1505 1506-1507-1508 1509-1510-1511 1512-1513-1514 1515-1516-1517 1518-1519-1520 1521-1522-1523 1524-1525-1526 1527-1528-1529 1530-1531-1532 1533-1534-1535 1536-1537-1538 1539-1540-1541 1542-1543-1544 1545-1546-1547 1548-1549-1550 1551-1552-1553 1554-1555-1556 1557-1558-1559 1560-1561-1562 1563-1564-1565 1566-1567-1568 1569-1570-1571 1572-1573-1574 1575-1576-1577 1578-1579-1580 1581-1582-1583 1584-1585-1586 1587-1588-1589 1590-1591-1592 1593-1594-1595 1596-1597-1598 1599-1600-1601 1602-1603-1604 1605-1606-1607 1608-1609-1610 1611-1612-1613 1614-1615-1616 1617-1618-1619 1620-1621-1622 1623-1624-1625 1626-1627-1628 1629-1630-1631 1632-1633-1634 1635-1636-1637 1638-1639-1640 1641-1642-1643 1644-1645-1646 1647-1648-1649 1650-1651-1652 1653-1654-1655 1656-1657-1658 1659-1660-1661 1662-1663-1664 1665-1666-1667 1668-1669-1670 1671-1672-1673 1674-1675-1676 1677-1678-1679 1680-1681-1682 1683-1684-1685 1686-1687-1688 1689-1690-1691 1692-1693-1694 1695-1696-1697 1698-1699-1700 1701-1702-1703 1704-1705-1706 1707-1708-1709 1710-1711-1712 1713-1714-1715 1716-1717-1718 1719-1720-1721 1722-1723-1724 1725-1726-1727 1728-1729-1730 1731-1732-1733 1734-1735-1736 1737-1738-1739 1740-1741-1742 1743-1744-1745 1746-1747-1748 1749-1750-1751 1752-1753-1754 1755-1756-1757 1758-1759-1760 1761-1762-1763 1764-1765-1766 1767-1768-1769 1770-1771-1772 1773-1774-1775 1776-1777-1778 1779-1780-1781 1782-1783-1784 1785-1786-1787 1788-1789-1790 1791-1792-1793 1794-1795-1796 1797-1798-1799 1800-1801-1802 1803-1804-1805 1806-1807-1808 1809-1810-1811 1812-1813-1814 1815-1816-1817 1818-1819-1820 1821-1822-1823 1824-1825-1826 1827-1828-1829 1830-1831-1832 1833-1834-1835 1836-1837-1838 1839-1840-1841 1842-1843-1844 1845-1846-1847 1848-1849-1850 1851-1852-1853 1854-1855-1856 1857-1858-1859 1860-1861-1862 1863-1864-1865 1866-1867-1868 1869-1870-1871 1872-1873-1874 1875-1876-1877 1878-1879-1880 1881-1882-1883 1884-1885-1886 1887-1888-1889 1890-1891-1892 1893-1894-1895 1896-1897-1898 1899-1900-1901 1902-1903-1904 1905-1906-1907 1908-1909-1910 1911-1912-1913 1914-1915-1916 1917-1918-1919 1920-1921-1922 1923-1924-1925 1926-1927-1928 1929-1930-1931 1932-1933-1934 1935-1936-1937 1938-1939-1940 1941-1942-1943 1944-1945-1946 1947-1948-1949 1950-1951-1952 1953-1954-1955 1956-1957-1958 1959-1960-1961 1962-1963-1964 1965-1966-1967 1968-1969-1970 1971-1972-1973 1974-1975-1976 1977-1978-1979 1980-1981-1982 1983-1984-1985 1986-1987-1988 1989-1990-1991 1992-1993-1994 1995-1996-1997 1998-1999-2000 2001-2002-2003 2004-2005-2006 2007-2008-2009 2010-2011-2012 2013-2014-2015 2016-2017-2018 2019-2020-2021 2022-2023-2024 2025-2026-2027 2028-2029-2030 2031-2032-2033 2034-2035-2036 2037-2038-2039 2040-2041-2042 2043-2044-2045 2046-2047-2048 2049-2050-2051 2052-2053-2054 2055-2056-2057 2058-2059-2060 2061-2062-2063 2064-2065-2066 2067-2068-2069 2070-2071-2072 2073-2074-2075 2076-2077-2078 2079-2080-2081 2082-2083-2084 2085-2086-2087 2088-2089-2090 2091-2092-2093 2094-2095-2096 2097-2098-2099 2100-2101-2102 2103-2104-2105 2106-2107-2108 2109-2110-2111 2112-2113-2114 2115-21

Case Study # 4
Keystone Drive/
Lake Pineloch
(Geysering)




Keystone Drive
(geysering)

Case Study # 5

Big Sand Lake

(Effective Lake Level Control)

Lake Level For Big Sand Lake (7/1/1959 to 8/19/2009)



Orange County's Perspective On Drainage Well Replacement

Presented by:


Maricela Torres

Chief Engineer

Orange County Public Works Dept.
(Roads & Drainage Division)


Drainage Wells Within Orange County Jurisdiction- Key Numbers:

- Total # of operational drainage wells within OC jurisdiction = 73
- Total # of abandoned drainage wells within OC jurisdiction = 8
- Total # of wells replaced by OC since 1998 = 24
- Total # of OC well replacement projects in progress = 15



Legend:

- Drainage Well Location

 <p>DEVO Engineering CONSULTING GEOTECHNICAL ENGINEERS</p> <p>5500 Alhambra Drive, Orlando, Florida 32808 Phone: (407) 296-2371 Fax: (407) 298-9011 E-mail address: devo@devoeng.com Website: http://www.devoeng.com</p>		Figure Name: Active Drainage Wells Maintained By Orange County	
		Project Name:	
Checked & Approved By: DS	Drawn By: RDC	Date: 02-15-2010	Scale: Noted
			Project #: Figure 1

Orange County's Guidance Principles for Replacement Well Projects:

- ensure the replacement well provides at least the same level of flood protection for citizens
- provide a replacement well which is built to the current water well construction standards to prevent inter-aquifer leakage and sinkhole development due to soil loss, and preserve aquifer recharge
- Require easements and access for maintenance by county's crew
- Design drainage structures with flashboards (for pre-storm bleed-down) and provide a water quality improvement where possible

Typical Design & Construction Phases for Replacement Wells:

- Clean, video logging, geophysical logging, and preliminary inspection of well conditions, prior to initiating any consultant studies for replacement.
- Phase 1A studies (mandatory) to obtain concept approval from FDEP before proceeding into the expense of detailed design
- Phase 1B studies (optional) which may emanate from the 1A task, if, for example, FDEP requests a groundwater quality/tracer study to investigate potential linkage between the drainage well and potable wells within Area of Review. A small area drainage study is also sometimes required if the well is shifted.
- Phase 2 follows Phase 1 concept approval by FDEP and involves preparation of detailed plans and specs for bidding the work through the county's procurement process. County does not want to expend funds on design until it is certain the FDEP will approve the replacement.
- Phase 3 involves construction oversight and load testing of the completed replacement well; Phase 3b may involve modifications to the plans during construction as geologic anomalies are sometimes encountered during well drilling.
- An occasional emergency well replacement due to flooding or well-induced sinkhole activity

Orange County Maintenance Program for Existing Wells:

- Well cleaning initiated based on maintenance personnel observations
- Routine cleaning of intake structures at well head and at lake, including channel entrances
- Routine checks on well head and bird cages
- React to resident's complaints of geysering or other well dysfunction including land subsidence
- Update the database with inspection details
- Adjust variable weirs prior to major storms

Budgeting Process for Drainage Well Replacement Projects:

- Less than \$1M/Fiscal Year for design and construction of drainwell replacements
- Critical drainage wells are given a higher priority on the replacement list
- Funding on a case by case basis for emergency projects
- Operations budget for routine maintenance and cleaning

FDEP Permitting Criteria & Regulations

Presented by:

Duane Watroba

Permitting Compliance and Enforcement
FDEP (Central District), UIC Program

FDEP Permitting Criteria (1 of 2):

- Stormwater/lake level control drainage wells in Orange County are classified as Group 6-Class V injection wells per Chapter 62-528 of Florida Administrative Code (F.A.C.) titled Underground Injection Control (date of most recent version: October 9, 2008).
- Florida Department of Environmental Protection (FDEP) obtained delegation of the Underground Injection Control (UIC) program from EPA on March 9, 1983, following the adoption of Federal UIC regulations (tailored for Florida) via Chapter 17-28, F.A.C. which was effective on April 1, 1982.
- Chapter 17-28 F.A.C. recognized that many Class V (Group 6) wells existed prior to the adoption of state and federal UIC rules and therefore "grandfathered" all drainage wells which were operating prior to April 1, 1982.
- The pre April 1982 wells may continue to operate without a permit as long as they work as intended. However, if an existing well needs to be modified or restored to its original condition (or better), a permit will be needed per the requirements of 62-528.

FDEP Permitting Criteria (2 of 2):

- A detailed well inventory is required as part of the permit application for conceptual approval of a Class V (Group 6) replacement well. The inventory must cover an "area of review" which is defined as the project area plus a circumscribing area with a fixed width of not less than one mile.
- The inventory encompasses more than a count of wells; it includes an evaluation of the hydrogeology in this locality, ground water flow direction, ground water quality, future usage, etc. Many different professionals are involved in this process including an engineer to process all the well data in the area, GIS locations from water management district databases, field technicians for door to door review of wells within the review area, and hydrogeologists to review well lithology and groundwater quality characteristics and water use in the locality.
- If the well inventory is not comprehensive and/or lacks sufficient detail and explanation, the FDEP may require a groundwater monitoring program as part of the drainage well replacement project. They may even deny the permit if there is a major concern.

Discussion of Well Inventory for Class V (Group 6) Drainage Well Replacement (1 of 2):

➤ The following is a list of services which are typically performed by consultant as part of the well inventory process:

1. preparation of a high resolution color aerial in 24" by 36" format to delineate the area of review and to be used in the field investigation (the aerial date is usually 2007 or 2008);
2. door to door inventory of wells and potential pollution sources within the area of review;
3. download of GIS database from SFWMD and SJRWMD for the specified coverage
4. review and quality control of the downloaded well databases as there are frequently non-functional or abandoned potable wells which are relic in the database and need to be purged;
5. plot and tabulate GIS-inventoried wells and include in the field verification exercise;

Discussion of Well Inventory for Class V (Group 6) Drainage Well Replacement (2 of 2):

6. map ground water flow direction in Upper Floridan aquifer from published sources and identify wells which are upgradient and downgradient of the replacement well project;
7. where necessary, review city/county connections for potable water supply delivery;
8. where necessary, interview the owner of the potential impacted well to verify well details and water quality and future use of any well which may be impacted;
9. where necessary, review the thickness of the confining layer above the Upper Floridan aquifer if there is a concern about migration of contaminants from the surficial aquifer or added sources of contamination which recharge the well at the replacement location;
10. where necessary, review groundwater quality data in the Floridan aquifer;

Discussion of Well Inventory for Class V (Group 6) Drainage Well Replacement:

- where necessary, review lithologic well logs to check the flow zones and potable withdrawal zones in the Upper Floridan aquifer; and
- address potential wellfield impacts with FDEP prior to preparation of the justification report if any sensitive wells show up in the inventory;

Design and permitting Special Problems

Presented by:

Dave Kincaid, P.G.


Hydrogeology Manager

Devo Engineering

Some Problems During Well Construction:

- ❖ Sinkholes forming due to soil loss at the drainage well casing/soil interface. Note: no grout seal around the old well casings and some of the wells are short cased in the Hawthorn
- ❖ Many wells are within natural depressions in the landscape and some of these areas are characterized by deep deposits of muck (>200 ft) which results in aborting well construction and moving to a new location or deeper well casing
- ❖ A similar situation as above but with flowing sand and debris from deep cavities in the rock. Note that the old wells create enlarged flow channels in the aquifer and the proximate replacement well may intersect these enhanced flow channels.
- ❖ Borehole collapse (unstable rock) or large sand filled cavities which prevent advancement of the borehole
- ❖ Geysering of newly constructed wells due to extremely high transmissivity in the Floridan aquifer and high intake capacity from lake.

Clay Street Drainage Well Replacement Plan



Example of Street Level Control Well – Clay St. (1 of 4)



Clay Street - CDS stormwater treatment unit prior to installation.

Example of Street Level Control Well – Clay St. (2 of 4)



Clay Street - Additional view of CDS and drainage well structures.

Example of Street Level Control Well – Clay St. (3 of 4)




Clay Street - Oil baffle and separation screen within CDS structure.

Example of Street Level Control Well – Clay St. (4 of 4)



Clay Street - Access hatch and manhole cover for drainage well and weir structure.



Goddard Street
Drainage Well
Replacement Plan

Example of Canal Level Control Well – Goddard Ave. (1 of 5)



Goddard Avenue - Old headwall structure showing well intake (L) and roadway discharge (R)

Example of Canal Level Control Well – Goddard Ave. (2 of 5)



Goddard Avenue - Structure and pipe installations prior to backfilling.

Example of Canal Level Control Well – Goddard Ave. (3 of 5)



Goddard Avenue - Interior of DW-031 well structure.

Example of Canal Level Control Well – Goddard Ave. (4 of 5)




Goddard Avenue - Unstable ditch sideslope - note soil cracking.

Example of Canal Level Control Well – Goddard Ave. (5 of 5)



Goddard Avenue - Cable concrete ditch enhancement installed by Orange County personnel.



Bumby Avenue
Drainage Well
Replacement Plan

Example of Pond Level Control Well – Bumby Ave. (1 of 3)



Bumby Avenue - Turbidity barriers being set up prior to construction activities.

Example of Pond Level Control Well – Bumby Ave. (2 of 3)




Bumby Avenue - Backfilling and compacting area around new well enclosure.

Example of Pond Level Control Well – Bumby Ave. (3 of 3)



Bumby Avenue - Fiberglass skimmer being set into position on inflow structure.

Bass Lake Drainage Well Replacement Plan



Example of Lake Level Control Well – Bass Lake (1 of 4)



Bass Lake - View of 18-inch diameter surface casing being driven to depth using a pneumatic hammer.

Example of Lake Level Control Well – Bass Lake (1 of 4)



Bass Lake - Closeup view of 12-inch diameter drill bit.

Example of Lake Level Control Well – Bass Lake (1 of 4)



Bass Lake - View of headwall during installation activities.

Example of Lake Level Control Well – Bass Lake (1 of 4)



Bass Lake - View of enclosure being installed.

Example of Lake Level Control Well – Bass Lake (1 of 4)



Bass Lake - View of trackhoe-mounted hammer during sheet pile wall installation.

Example of Lake Level Control Well – Bass Lake (1 of 4)



Bass Lake - Complete sheetpile wall with end wall and skimmer

Example of Lake Level Control Well – Bass Lake (2 of 4)



Bass Lake - View showing enclosure with aluminum hatch at new well.

Selected list of references For drainage well In central florida

Provided by:
Devo Engineering

Selected References - Floridan Aquifer Drainage Wells in Central Florida

Black, Crow, and Eidsness/CH2M Hill. September 1977. A Preliminary Assessment of the Drainage Well Situation in the Orlando Area. E.E. Shannon and M.P. Wanielista - editors. Gainesville, FL: Report No. 862-7601-4 prepared for East Central Florida Regional Planning Council, Winter Park, FL.

Bradner, L.A. 1991. Water Quality in the Upper Floridan Aquifer in the Vicinity of Drainage Wells, Orlando, Florida. U.S. Geological Survey Water Resource Investigations Report 90-4175. Tallahassee, Florida.

Bradner, L.A. 1996. Estimation of Recharge Through Selected Drainage Wells and Potential Effects from Well Closure, Orange County, Florida. WRI 96-316. Tallahassee, Florida: U.S. Geological Survey.

CH2M HILL. 1998. Central Florida Artificial Recharge Demonstration Program: Alternative Water Supply Strategies in the St. Johns River Water Management District. Special Publication SJ98-SP11. SJRWMD. Palatka, FL.

CH2M HILL. 2007. Central Florida Aquifer Recharge Enhancement Program Phase 1 –Artificial Recharge Well Demonstration Project. Special Publication SJ2007-SP11. SJRWMD. Palatka, FL.

Hartman and Associates, Inc. 2003. South Florida Water Management District Drainage Well Inventory for Orange, Seminole and Lake Counties. Orlando, FL.

Kimrey, Joel O. 1978. Preliminary Appraisal of the Geohydrologic Aspects of Drainage Wells, Orlando Area, Central Florida. Tallahassee. U.S. Geological Survey Water-Resources Investigations Report 78-37 prepared in cooperation with Florida Department of Environmental Regulation.

Selected References - Floridan Aquifer Drainage Wells in Central Florida

Kimrey Joel O. and Fayard, Larry D. 1984. Geohydrologic Reconnaissance of Drainage Wells in Florida. Tallahassee: U.S. Geological Survey Water-Resources Investigations Report 84-4021 prepared in cooperation with the Florida Department of Environmental Regulation.

McBee, J.M. 1985. The Quantity of Storm water Entering the Drainage Wells of Orlando, Florida. M.E. Thesis. Orlando, Florida: University of Central Florida.

Schiner, George R. and German, Edward R. 1983. Effects of Recharge from Drainage Wells on Quality of Water in the Floridan Aquifer in the Orlando Area, Central Florida. Tallahassee: U.S. Geological Survey Water-Resources Investigations Report 82-4094, prepared in cooperation with the Florida Department of Environmental Regulation.

Unklesbay, A. G., and Cooper, H. H., 1946, Artificial recharge of artesian limestone at Orlando, Florida: Economic Geology no. 4, June-July, 1946, p. 293-307.

U.S. EPA. September 1999. The Class V Underground Injection Control Study. Volume 3, Storm Water Drainage Wells